



Specifications Ledvance LED  
Downlight Alu DN200 35W 3150lm  
100D - 840 Cool White | 215mm - IP44

[View Product](#)

## General Information

|                      |                                |
|----------------------|--------------------------------|
| SKU                  | 233343                         |
| EAN                  | 4058075091573                  |
| Manufacturer Code    | 4058075091573                  |
| Brand                | Ledvance                       |
| Manufacturer Name    | DL ALU DN200 35W/4000K WT IP44 |
| Budgetlight warranty | 5 Years                        |
| Average Lifetime (h) | 50000                          |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x42              |
| Wattage                     | 35W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                         |                                       |
|-------------------------|---------------------------------------|
| Light colour options    | Single Color                          |
| Driver Included         | Yes                                   |
| Beam Angle (degree)     | 100                                   |
| Luminous Flux (Lumen)   | 3150lm                                |
| Lumen per watt          | 90                                    |
| Power factor            | >0.90                                 |
| Installation Depth (mm) | 120                                   |
| Unified Glare Rating    | < 28 - for hallways and storage rooms |
| Optical Cover           | PMMA (Polymethyl methacrylate)        |
| Suitable for Outdoor    | No                                    |
| Product Type Category   | LED Downlight                         |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Recessed                      |
| Cut out (mm)           | 200                           |
| IP-rating              | IP44                          |
| Impact Protection (IK) | IK02 - 0.20 joule             |
| Operating Temperature  | -20 to +45                    |
| Housing                | Aluminium                     |
| Colour of the Fixture  | White                         |
| Colour of material     | White                         |
| Fixture Connection     | PI [Push-in connector 2-pole] |
| Product Serie          | DOWNLIGHT ALU                 |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 61  |
| Diameter (mm) | 215 |

## Sensor Information

---

Type of sensor

No Sensor

## Why Budgetlight?



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**