



**Specifications Ledvance LED  
Downlight Comfort UGR19 Aluminium  
30W/25W/20W  
3600lm/3000lm/2400lm 100D -  
930-940 CCT | Cutout 200mm- IP44 -  
Best Colour Rendering**

[View Product](#)

## General Information

|                      |                                       |
|----------------------|---------------------------------------|
| SKU                  | 254960                                |
| EAN                  | 4099854491122                         |
| Manufacturer Code    | 4099854491122                         |
| Brand                | Ledvance                              |
| Manufacturer Name    | DL CMFT D200 P 30W MS 940 U19 WT LEDV |
| Budgetlight warranty | 5 Years                               |
| Average Lifetime (h) | 100000                                |

## Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 2x26              |
| Wattage                     | 30W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 930 Warm White    |
| Colour temperature (Kelvin) | 3000 Warm White   |
| Colour Rendering (Ra)       | 90-99             |

|                       |                    |
|-----------------------|--------------------|
| Colour of Light       | White              |
| Light colour options  | Single Color       |
| Beam Angle (degree)   | 55                 |
| Luminous Flux (Lumen) | 3600lm             |
| Lumen per watt        | 120                |
| Power factor          | >0.90              |
| Unified Glare Rating  | < 19 - For offices |
| Optical Cover         | Opal               |
| Product Type Category | LED Downlight      |

## Fixture Information

|                        |                        |
|------------------------|------------------------|
| Mounting Method        | Recessed               |
| Cut out (mm)           | 200                    |
| IP-rating              | IP44                   |
| Impact Protection (IK) | IK03 - 0.35 joule      |
| Operating Temperature  | -20 to +40             |
| Housing                | Aluminium              |
| Colour of the Fixture  | White                  |
| Fixture Connection     | PI [Push-in connector] |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 117 |
| Diameter (mm) | 215 |

**Sensor Information**  Guaranteed **budget prices**  Up to **7 years warranty**

Type of sensor  **Easy** return process  No Sensor  Long-life **LED solutions**