



**Specifications Ledvance LED  
Downlight Universal White 18W  
2350lm 110D - 830-840 CCT | Cutout  
65-260mm - IP44 - Dali Dimmable**

[View Product](#)

## General Information

|                      |                                                 |
|----------------------|-------------------------------------------------|
| SKU                  | 256471                                          |
| EAN                  | 4099854541339                                   |
| Manufacturer Code    | 4099854541339                                   |
| Brand                | Ledvance                                        |
| Manufacturer Name    | DOWNLIGHT UNIVERSAL DALI D200 V 18W ML 83040 WT |
| Budgetlight warranty | 5 Years                                         |
| Average Lifetime (h) | 100000                                          |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Emergency Lighting          | No Emergency Unit                |
| Tiltable                    | No                               |
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 150                              |
| Wattage                     | 18W                              |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Dimmable with Dali               |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |

|                       |                          |
|-----------------------|--------------------------|
| Light colour options  | CCT                      |
| Beam Angle (degree)   | 110                      |
| Luminous Flux (Lumen) | 2350lm                   |
| Lumen per watt        | 131                      |
| Power factor          | >0.90                    |
| Unified Glare Rating  | < 23 - for general areas |
| Optical Cover         | Opal                     |
| Product Type Category | LED Downlight            |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 65x260            |
| IP-rating              | IP44              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +40        |
| Housing                | Plastic           |
| Colour of the Fixture  | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 22  |
| Diameter (mm) | 217 |

## Sensor Information

## Why Budgetlight?

Type of sensor

No Sensor



Guaranteed **budget prices**



Up to **7 years warranty**



**Easy** return process



Long-life **LED solutions**